

SUNDREAM

TRANSPARENT F/R MEMBRANE

ROLL WIDTH	204cm		
ROLL LENGTH	50m		
NOMINAL WEIGHT	790gsm		
FABRIC TYPE	PVC coated material with woven polyester scrim		
SURFACE FINISH	PVDF lacquer top surface / Acrylic lacquer under surface		
FIRE RETARDANT	AS/NZS 1530.2 & AS/NZS 1530.3		
TENSILE STRENGTH Warp/Weft	2300 / 2200 N/5cm		
TEAR STRENGTH Warp/Weft	170 / 160 N		
ADHESION	150 N/5cm		
U/V WARRANTY	10 year limited		
ELONGATION AT BREAK Warp/Weft	18% / 25%		
FABRICATION METHODS	Hot Wedge, Hot Air or High Frequency Welding: Sewing		
TEMPERATURE RANGE	-30° / +60° C		
FABRIC CARE	OFPANZ Care Label OF-1		
	SX 1800-H (A) CLEAR	SX 1800-C (A) COOL	SX 1800-H (A) CHARCOAL
LIGHT TRANSMISSION	62%	52%	32%
UV-A Block	99.6%	99.7%	99.6%
UV-B Block	99.9%	99.9%	99.9%